

**KANSAS DEPARTMENT OF TRANSPORTATION
SPECIAL PROVISION TO THE
STANDARD SPECIFICATIONS, EDITION 2015**

Delete SECTION 1729 and replace with the following:

SECTION 1729

ANTI-GRAFFITI COATINGS

1729.1 DESCRIPTION

This specification covers anti-graffiti coatings, which are coatings applied to substrates to facilitate the removal of graffiti.

1729.2 REQUIREMENTS

a. General.

(1) Anti-graffiti coatings must be non-sacrificial and not cause damage to above grade concrete, concrete block, exposed aggregate concrete, brick, stonework, painted steel, or aluminum substrates.

(2) The applied coating must produce a firm, continuous, uniform film that is free of pinholes, cracks, or other film defects and exhibit satisfactory adhesion. The consistency must be such that the coating can be satisfactorily applied by spray, roller, or brush at atmospheric and material temperatures above 50°F without thinning. When applied properly to vertical surfaces, the coating must remain uniform during the required curing period and must not sag, disintegrate, check, peel, or crack.

(3) The VOC content of the coating must comply with the current Environmental Protection Agency (EPA) Title 40, Code of Federal Regulations (40 CFR) for industrial maintenance coatings.

(4) The color must match Federal Standard 595B, color number 35630 unless otherwise shown in the Contract Documents. When the Contract Documents specify another color, the color must match the color standard supplied by the Engineer. The Contract Documents may specify clear or translucent as a color.

Provide material complying with the requirements listed in **TABLE 1729-1**.

Property	Test Method	Requirement
Graffiti Resistance	ASTM D7089	Cleanability Level 1 or 2
Recleanability	ASTM D7089	Min. 5 cycles
Set-to-Touch Time	ASTM D1640 ^a	4 hr. maximum
Dry-Through Time	ASTM D1640 ^a	24 hr. maximum

^a Use Method A

1729.3 TEST METHODS

Test in accordance with the requirements stated in **subsection 1729.2**.

1729.4 PREQUALIFICATION

a. Each anti-graffiti coating intended for use under this specification must be prequalified before use. Submit a written request for prequalification to the Bureau Chief of Construction and Materials. Provide the following documentation:

(1) Name, address, and telephone number of the manufacturer. Include the name and e-mail address of the preferred contact person.

(2) Brand name of the anti-graffiti coating.

(3) A complete description, literature, infrared spectrum, and set of instructions for removal of graffiti.

(4) Safety Data Sheets.

b. Submit a one-gallon sample from production and detailed installation instructions to the Engineer of Tests. All coatings will be tested in accordance with **subsection 1729.2.** and will be fingerprinted using infrared spectroscopy for use in screening future verification samples to verify that materials submitted for use are of an identical formulation as originally approved.

c. The information, test reports and test results obtained at the Materials and Research Center on samples submitted, will be reviewed by the Bureau Chief of Construction and Materials. The manufacturer will be advised of the results.

d. The Bureau of Construction and Materials will maintain a list of prequalified products. Products that have been prequalified will remain prequalified if the formulation and manufacturing processes remain unchanged, and field experience indicates that the anti-graffiti coating functions appropriately. Changes in formulation or manufacturing processes will require new prequalification testing.

Failure of the material to function appropriately in the field will be cause for removal of the product from prequalified status. Products removed from prequalified status will be considered for requalification if the manufacturer can provide evidence that the cause of failure has been positively identified, and necessary formulation changes and/or quality control measures have been implemented to prevent future failures. Complete prequalification testing may be required for products that have been removed from prequalified status.

1729.5 BASIS OF ACCEPTANCE

Prequalification as specified in **subsection 1729.4.**

Receipt and approval of a Type C certification as specified in **DIVISION 2600.**

10-01-20 C&M (KJS)
Mar-2021 Letting